

KALWALL® PERFORMANCE TABLES

FACE SHEET COMBINATIONS		PANEL 'U' VALUE – LALLS – LLM ² K PANEL THICKNESS 70MM										PANEL 'U' VALUE – LALLS – LLM ² K PANEL THICKNESS 100MM						INTERNAL FLAME SPREAD
THERMALLY BROKEN		2.57		1.25		0.78		0.56		0.28*		2.85		0.83		0.45		
STANDARD		2.74		1.56		1.20		0.99		0.72*		N/A		N/A		N/A		
EXTERIOR	INTERIOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	
White SW-C	White B-3A	20	0.31	14	0.16	8	0.10	5	0.07	9	0.08	20	0.31	12	0.13	5	0.06	CLASS O
Crystal SW-C	White B-3A	30	0.38	20	0.19	10	0.12	6	0.07	12	0.11	30	0.38	13	0.15	5	0.07	CLASS O

FACE SHEET COMBINATIONS		PANEL 'U' VALUE – LOOFS – OFM ² K PANEL THICKNESS 70MM										PANEL 'U' VALUE – LOOFS – OFM ² K PANEL THICKNESS 100MM						INTERNAL FLAME SPREAD
THERMALLY BROKEN		2.86		1.31		0.80		0.57		0.28*		3.22		0.86		0.46		
STANDARD		3.08		1.67		1.26		1.03		0.74*		N/A		N/A		N/A		
EXTERIOR	INTERIOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	LIGHT TRANS	SOLAR FACTOR	
White SW-C	White B-3A	20	0.28	14	0.15	8	0.09	5	0.06	9	0.08	20	0.28	12	0.12	5	0.05	CLASS O
Crystal SW-C	White B-3A	30	0.35	20	0.18	10	0.11	6	0.07	12	0.10	30	0.35	13	0.14	5	0.06	CLASS O

NOTES:-

- Solar Factor is total Solar Heat Transmittance.
- 'U' Values are calculated according to CIBSE Guide Volume A Chapter 3.
- Light transmissions are expressed in percentage terms.
- Light transmissions over 30% are not recommended for normal use.
- All performance figures based on 600mm by 300mm internal panel grid.
- Internal Flame Spread in accordance with BS 476 Parts 3, 6 and 7.
- Other face sheet combinations available on request.

*Kalwall + Nanogel®

Please consult Stoakes Systems Limited on 020 8660 7667 for further clarification and guidance.